

Multi-Purpose Fume Extraction System

Technical Data

Filter Cartridges: (1) Cellulose Flame Retardant Media

Motor/Blower: 1.5 HP, Direct Drive, Backward Incline Blower

Electrical Requirements: 1 Ph: 120v

Air Flow: 1,200 CFM

Downdraft Table FPM: 400

Built-in Spark Arrestance: (1) 14"x14"x2"

Metal Mesh (1) Spark Baffle

Cleaning System: (1) Continuous Air

Stream Cleaning system for 6-7 times filter life.

Compressed Air Requirements: 1" NPT compressed air connection; 70-90 PSI Required

Silencing: Internal Noise Abatement in Motor/Blower Compartment, 60-74 DBA

Weight: 215 lbs (no Fume Arm)

Dimensions: 76.86" x 36.06" x 42"

Conversion

Converts to wall mount or ground mount (portable configuration) out of the box with no additional accessories. 3 in 1 option allows for conversion from wall mount, to ground mount, to Downdraft Table



Accessories

Downdraft Table
(both parts come separately)

Magnetic Tool Tray

Features

Maximum Air Velocity

Low Noise

Unique Cleaning System

Easy To Use & Move

Applications

Welding

Dust Collection

The Fume Dog Fume Extractor Comes out of the Box Ready for These Configurations